

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently amended) An apparatus for printing a medical image on a recording medium, comprising:

a printing section to print either said medical image or a test-pattern for evaluating a quality of said medical image, on said recording medium, based on image data;

a printing-condition setting section to set a printing condition for printing said test-pattern; and

a printing-condition displaying section to display said printing condition set by said printing-condition setting section;

wherein said printing section prints at least one of a sharpness-evaluating pattern and a granularity-evaluating pattern~~[[.]], and~~

wherein said sharpness-evaluating pattern includes at least four kinds of pattern elements.

2. (Original) The apparatus of claim 1, further comprising:

an image data creating section to create a new image data based on said printing condition set by said printing-condition setting section.

3. (Original) The apparatus of claim 1, further comprising:  
a storing section to store said image data; and  
wherein said storing section stores at least one set of image data corresponding to said test-pattern to be printed on said recording medium.
4. (Previously presented) The apparatus of claim 1,  
wherein a plurality of test-patterns, being substantially the same to each other, can be printed on said recording medium.
5. (Original) The apparatus of claim 4,  
wherein border lines between said plurality of test-patterns are also printed on said recording medium.
6. (Previously presented) The apparatus of claim 1,  
wherein said printing-condition setting section includes a density-setting section to set a density of said medical image, based on a combination of at least two of the following factors including: a maximum density ( $D_{max}$ ) of said test-pattern in terms of either a transmission density or a reflection density; a minimum density ( $D_{min}$ ) of said test-pattern corresponding to said maximum density ( $D_{max}$ ); an average value ( $D_{ave}$ ) of said maximum density ( $D_{max}$ ) and said minimum density ( $D_{min}$ ); and a density difference  $\Delta D$ , where  $\Delta D = D_{max} - D_{min}$ .

7. (Original) The apparatus of claim 6, further comprising:  
an image data creating section to create a new image data based on said density set by said density-setting section.
8. (Original) The apparatus of claim 6,  
wherein both said test-pattern and said density set by said density-setting section are printed on said recording medium.
9. (Original) The apparatus of claim 6, further comprising:  
a storing section to store said image data; and  
wherein said storing section stores at least one set of image data corresponding to said test-pattern to be printed on said recording medium.
10. (Previously presented) The apparatus of claim 9, further comprising:  
an image data selecting section to select any one of a plurality of image data sets, which are stored in advance in said storing section corresponding to densities set by said density-setting section; and  
wherein said storing section stores at least two of said image data sets, which are different each other in image-signal values so that test-patterns printed on said recording medium are substantially the same to each other except said densities.

11. (Original) The apparatus of claim 9, further comprising:  
an image data processing section to generate new image data sets  
corresponding to said densities by processing said image data sets stored in advance in  
said storing section.
12. (Original) The apparatus of claim 1,  
wherein said printing-condition setting section includes a pixel-size setting  
section to set a pixel-size of one pixel included in said image data; and  
further comprising:  
an interpolate-processing section to apply an interpolate-processing for either  
expansion or a reduction of said medical image to said image data, in response to said  
pixel-size set by said pixel-size setting section.
13. (Original) The apparatus of claim 12, further comprising:  
an image data creating section to create a new image data based on said pixel-  
size set by said pixel-size setting section.
14. (Previously presented) The apparatus of claim 12,  
wherein said printing-condition setting section includes an interpolate-processing  
method setting section to set an interpolate-processing method for either expanding or a  
reducing of said medical image.

15. (Previously presented) The apparatus of claim 12,  
wherein both said test-pattern and interpolate-processing information pertaining to said interpolate-processing applied by said interpolate-processing section are printed on said recording medium, and said interpolate-processing information includes at least one of the following factors including: said pixel-size, an interpolate-processing method, and an interpolate-scaling factor.
16. (Original) The apparatus of claim 12, further comprising:  
a storing section to store said image data; and  
wherein said storing section stores at least one set of image data corresponding to said test-pattern to be printed on said recording medium.
17. (Previously presented) The apparatus of claim 16, further comprising:  
an image data selecting section to select any one of a plurality of image data sets, which are stored in advance in said storing section corresponding to pixel-sizes set by said pixel-size setting section; and  
wherein said storing section stores at least two of said image data sets, which are different each other in an amount of image data so that test-patterns printed on said recording medium are substantially the same each other except image-sizes of said test-patterns.

18. (Original) The apparatus of claim 16, further comprising:  
an image data processing section to generate new image data sets  
corresponding to said pixel-sizes by processing said image data sets stored in advance  
in said storing section.
19. (Original) The apparatus of claim 1, further comprising:  
an image-direction setting section to set an image-direction of said medical  
image printed on said recording medium.
20. (Original) The apparatus of claim 19, further comprising:  
an image data creating section to create a new image data based on said image-  
direction set by said image-direction setting section.
21. (Original) The apparatus of claim 19,  
wherein both said test-pattern and information pertaining to said image-direction,  
set by said image-direction setting section, are printed on said recording medium.
22. (Original) The apparatus of claim 19, further comprising:  
a storing section to store said image data; and  
wherein said storing section stores at least one set of image data corresponding  
to said test-pattern to be printed on said recording medium.

23. (Previously presented) The apparatus of claim 22, further comprising:  
an image data selecting section to select any one of a plurality of image data sets, which are stored in advance in said storing section corresponding to image-directions, set by said image-direction setting section; and  
wherein said storing section stores at least two of said image data sets, which are different each other in said image-direction so that test-patterns printed on said recording medium are substantially the same each other except image-directions of said test-patterns.
24. (Original) The apparatus of claim 22, further comprising:  
an image data processing section to generate new image data sets corresponding to image-directions, set by said image-direction setting section, by processing said image data sets stored in advance in said storing section.
25. (Original) The apparatus of claim 1, further comprising:  
a pattern-number setting section to set a number of test-patterns to be printed on said recording medium.
26. (Original) The apparatus of claim 25,  
wherein a plurality of test-patterns can be printed on said recording medium.

27. (Previously presented) The apparatus of claim 26,  
wherein said printing-condition setting section includes a combination setting section to set a combination of test-patterns when said pattern-number setting section sets a number of said test-patterns, and said combination of said test-patterns is one of the following combinations of: different evaluating items, different densities, different pixel-sizes, different interpolate-processing methods, different interpolate-scaling factors, and different image-directions.
28. (Original) The apparatus of claim 26,  
wherein, when said pattern-number setting section sets a number of said plurality of test-patterns, border lines between said plurality of test-patterns are also printed on said recording medium.
29. (Currently amended) The apparatus of claim 1,  
wherein ~~said sharpness-evaluating pattern has more than four kinds of pattern elements~~, spatial frequencies of ~~[[which]]~~ said pattern elements are different relative to each other and in each of which 1 to 20 periods of each spatial frequency are aligned.
30. (Original) The apparatus of claim 29,  
wherein a spatial frequency of a normalized pattern element, being one of said pattern elements and having a lowest spatial frequency among them, is not greater than 0.5 cycle/mm.



31. (Original) The apparatus of claim 30,  
wherein 5 to 20 periods of each spatial frequency are aligned in each of said pattern elements other than said normalized pattern element.
32. (Original) The apparatus of claim 29,  
wherein a width of each of said pattern elements in a read-scanning direction is in a range of 10 to 200 mm.
33. (Original) The apparatus of claim 1, further comprising:  
a storing section to store said image data; and  
wherein said storing section stores at least one set of image data corresponding to said sharpness-evaluating pattern to be printed on said recording medium.
34. (Original) The apparatus of claim 33,  
wherein at least two sets of image data are stored in said storing section so that numbers of pattern elements in sharpness-evaluating patterns, to be printed on said recording medium, are different each other.
35. (Previously presented) The apparatus of claim 34, further comprising:  
an image data selecting section to select any one of a plurality of image data sets, which are stored in advance in said storing section corresponding to said numbers of said pattern elements.

36. (Original) The apparatus of claim 34, further comprising:  
an image data processing section to generate new image data sets  
corresponding to said numbers of said pattern elements by processing said image data  
sets stored in advance in said storing section.
37. (Original) The apparatus of claim 33, further comprising:  
an image data creating section to create a new image data based on a number of  
pattern elements in said sharpness-evaluating pattern.
38. (Original) The apparatus of claim 30,  
wherein said printing-condition setting section includes a spatial frequency  
setting section to set said spatial frequency of said pattern element.
39. (Previously presented) The apparatus of claim 38,  
wherein more than two image data sets with respect to sharpness-evaluating  
patterns, in which at least one of said more than two image data sets of spatial  
frequencies of pattern elements is different relative to each other, are stored in a storing  
section.
40. (Previously presented) The apparatus of claim 39, further comprising:  
an image data selecting section to select any one of said image data sets, which  
are stored in advance in said storing section corresponding to said spatial frequencies  
of said pattern elements.

41. (Previously presented) The apparatus of claim 38, further comprising:  
an image data processing section to generate new image data sets  
corresponding to spatial frequencies of pattern elements by processing said image data  
sets stored in advance in said storing section.
42. (Original) The apparatus of claim 29,  
wherein said printing-condition setting section includes a profiling-axis setting  
section to set a profiling-axis of a pattern element.
43. (Original) The apparatus of claim 42,  
wherein said profiling-axis setting section sets said profiling-axis at either a  
density, a lightness or a transmittance.
44. (Original) The apparatus of claim 42,  
wherein at least two of image data sets, which are different each other in image-  
signal values so that sharpness-evaluating patterns printed on said recording medium  
are substantially the same each other except said profiling-axis, are stored in a storing  
section.
45. (Previously presented) The apparatus of claim 42, further comprising:  
an image data selecting section to select any one of a plurality of image data  
sets, which are stored in advance in a storing section corresponding to said profiling-  
axis of said pattern elements.

46. (Original) The apparatus of claim 42, further comprising:  
an image data processing section to generate new image data sets  
corresponding to said profiling-axis of said pattern element by processing said image  
data sets stored in advance in a storing section.
47. (Original) The apparatus of claim 42, further comprising:  
an image data creating section to create a new image data based on said  
profiling-axis of said pattern element.
48. (Original) The apparatus of claim 29,  
wherein said printing-condition setting section includes a waveform setting  
section to set a waveform of a pattern element at either a rectangular wave, a chopping  
wave or a sine wave.
49. (Previously presented) The apparatus of claim 48, further comprising:  
an image data selecting section to select any one of a plurality of image data  
sets, which are stored in advance in a storing section corresponding to said waveform  
of said pattern element.
50. (Original) The apparatus of claim 48, further comprising:  
an image data processing section to generate new image data sets  
corresponding to said waveform of said pattern element by processing said image data  
sets stored in advance in a storing section.

51. (Original) The apparatus of claim 1,  
wherein said granularity-evaluating pattern has 3 to 20 uniform density regions,  
each of which has a uniform density being different from others and includes an area of  
5 mm X 5 mm but does not exceed an area of 200 mm X 200 mm.

52. (Original) The apparatus of claim 51,  
wherein said printing-condition setting section includes a density-region setting  
section to set a number of said uniform density regions.

53. (Previously presented) The apparatus of claim 52, further comprising:  
an image data selecting section to select any one of a plurality of image data  
sets, which are stored in advance in a storing section corresponding to said number of  
said uniform density regions set by said density-region setting section.

54. (Previously presented) The apparatus of claim 52,  
wherein, when design diffusion densities of said uniform density regions are not  
greater than 1.5, each line formed between said uniform density regions has a density  
not smaller than 2.0.

55-57. (Canceled)

58. (Original) The apparatus of claim 29,  
wherein said apparatus is a ink-jet printer, and said sharpness-evaluating pattern includes three or more pattern elements having a spatial frequency being equal to or more than 2.0 cycle/mm at a normalized portion.